

IN THE APPLICATION

OF

Gary M. McMurtry

and

Daniel N. Kokubun

FOR

Environmental Sampler for Mass Spectrometer

FILED WITH

THE UNITED STATES PATENT AND TRADEMARK OFFICE

**EXPRESS MAIL MAILING CERTIFICATE**

"Express Mail" mailing label number: EE354147395US

Date of Deposit 21 January 2002

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail" Post Office to Addressee" under 37 CFR 1.10 on the date indicated above and is addressed to "BOX PATENT APPLICATIONS, Assistant Commissioner for Patents, Washington, D.C. 20231"

Michael A. Kroil  
Attorney for Applicant

McMurtry Doc.No. GM-1-mv, 9 January 2002

# BACKGROUND OF THE INVENTION

## Field of the Invention

The present invention relates generally to sampling systems for mass spectrometers and, more specifically, to an environmental sampler for a mass spectrometer that allows for controlled introduction of small amounts of fluids or gases into the vacuum system of the mass spectrometer under severe environmental conditions. Accurate calibration checks of the sampler and mass spectrometer during remote autonomous operation is possible by means of an internal standard reservoir integral with the sampler of the present invention. A computer-controlled stepper motor moves a rod set which samples the external sample and the internal standard alternatively.

The forward motion of the rods (toward the outside of the pressure/vacuum housing) in predetermined numbers of steps samples the internal standard reservoir while the reverse motion of the rods (toward the

inside of the pressure housing) samples the external environment. The standard reservoir is designed to be at the same pressure as the external sample. This configuration provides a pressure-compensated rod set, reducing the mechanical forces on the stepper motor. This configuration also ensures a constant ratio of sample to standard volume and mass (approximately one to one). Hydraulic seals and O-rings keep external fluids and gases from entering the sampler, wherein surface-bound fluids and dissolved gases are evaporated from the sampler rod into the vacuum system. Dry gases (e.g. low moisture air) enter the sampler via small calibrated leaks in the rod during movement.

Initially, the sampler is mass spectrometer leak tight (no detectable flow). Flow into the sampler vacuum chamber is accomplished by engineering small calibrated leaks in the rod/seal system thereby permitting extremely small amounts of sample to be repeatedly and reliably introduced into the vacuum system of the mass spectrometer as the rods travel back and forth. This small sample capability reduces the pumping load on the vacuum system and permits extended in situ operation by virtue of its low power consumption. Its

operational pressure range (less than one atmosphere to greater than 400 atmospheres) allows autonomous operation in a variety of earth and planetary environments (outer space to full-ocean water depths).

A unique feature of the invention is the very small amount of sample acquired, which is rapidly expanded into a vapor prior to introduction to the mass spectrometer interface. Therefore, initial sample temperatures can be quite high without serious effect on the mass spectrometer. Temperature maximums are only dictated by the choice of polymers for the sampler seal and the plenum inlet hoses. Management of sample temperatures in excess of 200°C is possible if high temperature polymers such as silicon or teflon<sup>TM</sup> are used.

The present invention further includes a removeable external vacuum port to ambient that allows pumping and monitoring of a sample/standard waste vacuum within the mass spectrometer pressure housing. A removable external plenum allows directional flow of gas or fluid over the sampler rod pumped from a remote region of interest.

The present invention is primarily designed for a mass spectrometer, but it can be used in any application where small quantities of sample are needed from the environment, such as in gas or liquid chromatography, capillary electrophoresis, or any combination of these and other analytical techniques with mass spectroscopy.

## **Description of the Prior Art**

There are other samplers for mass spectrometers. Typical of these is U.S. Patent No. 4,201,913 issued to Bursack et al. on May 6, 1980.

Another patent was issued to Cassidy et al. on Jun. 7 1983 as U.S. Patent No. 4,386,852. Yet another U.S. Patent No. 4,562,351 was issued to Atherton et al. on Dec. 31, 1985 and still yet another was issued on May 20, 1986 to Gilles et al. as U.S. Patent No. 4,590,165.

Another patent was issued to Whistler on Jul. 22, 1986 as U.S. Patent No. 4,601,211. Yet another U.S. Patent No. 4,879,458 was issued to Brunfeldt et al. on Nov. 7, 1989. Another was issued to Spraul et al. on Mar. 14, 1995 as U.S. Patent No. 5,397,989 and still yet another was issued on Jan. 6, 1998 to Haner et al. as U.S. Patent No. 5,705,928.

Another patent was issued to Holle et al. on Nov. 24, 1998 as U.S. Patent No. 5,841,136. Yet another U.S. Patent No. 6,177,991 was issued to Okuda on

Jan. 23, 2001. Another was issued to Kenny et al. on Feb. 13, 2001 as U.S.

Patent No. 6,186,012 and still yet another was issued on Feb. 20, 2001 to

Hirabayashi et al. as 6,190,316.

U.S. Patent Number 4,201,913

Inventor: William W. Bursack et al.

Issued: May 6, 1980

An apparatus for introducing a gaseous sample into a mass spectrometer is disclosed which includes a hollow antechamber or cavity disposed between the sample stream and the high vacuum enclosure. Orifice openings are provided in the antechamber which allow the antechamber to communicate both with the high vacuum enclosure and the sample stream. An electrically operated pulsed valve is used to admit a series of small volumes of sample by pulses of controlled duration and frequency such that the sample flow from the antechamber into the high vacuum enclosure can be made to resemble one of essentially constant flow.



U.S. Patent Number 4,386,852

Inventor: Joseph A. Cassidy et al.

Issued: Jun. 7, 1983

A phase synchronization apparatus useful for synchronizing the sample signal and the demodulation signal at a spectrometer includes a stepper motor the position of which is controlled so that the desired phase synchronization is ensured.

U.S. Patent Number 4,562,351

Inventor: Paul Atherton et al.

Issued: Dec. 31, 1985

The invention consists of a mass spectrometer having a sample insertion probe on which a reference compound and an unknown sample can be simultaneously introduced without mixing into a field ionization or ion or neutral particle bombardment ion source. An insulated support is mounted by a parallel hinge on the end of the probe shaft. Two or more separated segments or emitter wires, one carrying the unknown sample, another carrying an appropriate reference compound, are mounted on a base member which is fitted to the support. A drive shaft, concentric with the outer probe shaft, has an eccentric peg on the end, which engages with a cam on the support, so that rotation of the drive shaft results in an oscillating motion of the segments or emitters, alternately positioning them in the optimum position for ionization. A spectrum of the sample or the reference compound can be obtained when required by selecting the appropriate position of the drive shaft. Rotation of the

McMurtry Doc.No. GM-1-mv, 9 January 2002

drive shaft may be controlled by a servo- mechanism and a computer. As a result, improved accuracy of mass measurement of peaks in the mass spectrum of the sample is achieved.

U.S. Patent Number 4,590,165

Inventor: Peter Gilles et al.

Issued: May 20, 1986

An automatic sampling method for introducing a diluted viscous sample into an instrument for analysis for trace elements. The automatic sampling system includes a tube assembly, a member for mounting the tube assembly in proper relation, means for maintaining, between sampling, the free end of the tube assembly in a cleaning solution, and means for inserting the free end of the tube assembly into a sample contained within a container. Preferably, the instrument is a spectrometer, the samples are organic and aqueous samples, such as oils, brines, sludges, plating solutions and the like, and the trace elements include wear metals and also other elements, such as calcium, barium, zinc, sodium, magnesium, boron, phosphor and the like.

U.S. Patent Number 4,601,211

Inventor: Wayne J. Whistler

Issued: Jul. 22 1986

A multi-port valve uses a flexible sample tube to selectively intercept gases flowing from inlet ports into a common manifold space. The manifold space is placed under sufficient vacuum to insure that gas samples will be selectively received by the sample tube when the sample tube is placed in close proximity to the selected inlet port to be sampled. The sample tube is arranged so that gases to be sampled from the selected port wash over the entrance end of the sample tube so that contaminated or mixed gases from the manifold space are prevented from entering the sample tube. The sample tube is mounted to pivot inside a valve body and is moved by a sample tube guide which rotates inside the valve body to selectively align the sample tube with the inlet ports. The valve body may be sealed by a cover through which the valve guide is driven to rotate by a magnetic coupling, or by a bearing seal through which the sample tube guide projects. The sample guide may be rotated in a stepwise

McMurtry Doc.No. GM-1-mv, 9 January 2002

fashion by a stepper motor for slow collection rates, or may be rotated quickly by a motor for rapid sampling. Magnetic detectors or a shaft decoder may be used to monitor the position of the sample tube guide. The multi-port valve may be used in a system in which a measuring device such as a mass spectrometer and a data system are used.

U.S. Patent Number 4,879,458

Inventor: Robert J. Brunfeldt

Issued: Nov. 7, 1989

An automated sample inlet system for sequentially introducing a plurality of indium encapsulated samples into a mass spectrometer wherein the samples are placed in a micro tube and loaded into a circular carousel under a vacuum bell jar maintained at ambient temperature. The samples are systematically advanced by rotating the carousel resulting in each sample sequentially falling through a delivery tube containing an inverted ball valve into a sample vaporizing chamber within an oven. An additional pair of sapphire ball valves in communication with the glass vaporizing chamber are sequentially opened and closed in a preprogrammed manner along with the opening and closing of the thermal inverted ball valve and the indexing of the carousel such as to automatically evacuate the glass inlet system within the oven, introduce a new sample and vaporize it and then inject this vapor into a mass spectrometer. Such

McMurtry Doc.No. GM-1-mv, 9 January 2002

a system is useful in running large numbers of mass spectrometer analyses of hydrocarbon liquids and the like.

McMurtry Doc.No. GM-1-mv, 9 January 2002



U.S. Patent Number 5,397,989

Inventor: Manfred Spraul et al.

Issued: Mar. 14, 1995

An NMR spectrometer (10) for the measurement of liquid samples having a probe head (20) exhibiting an upper and a lower support (21 or 22), a connector (5) for a feed conduit (15) for the introduction of a liquid sample (1) into the spectrometer (10) and a connector (6) for a drain conduit (16) for the drainage of the liquid sample (1) out of the spectrometer (10), a sample tube (3), arranged between the upper and the lower supports (21 or 22), for the acceptance of the fluid sample (1), whereby the one end of the sample tube (3) is connected to the connector (5) for the feed conduit (15) and the other end to the connector (6) for the drain conduit (16), exhibits, coaxially to the sample tube (3) a further tube (4) for the acceptance of a calibration fluid (2) which, on one end, is connected to an additional connector (7) for a feed conduit (17) to introduce the calibration fluid (2) into the spectrometer (10) and, on its other end, to an additional connector (8) for a drain conduit (18) to drain the

McMurtry Doc.No. GM-1-mv, 9 January 2002

calibration fluid (2) out of the spectrometer (10). In this manner, it is possible to measure the sample fluid (1) in a simple fashion, without the previous mixing of additives and, subsequent to the measurement, to regain the sample fluid in its original state, while allowing for the introduction of a calibration fluid (2) for field stabilization and for the quantitative comparison of line intensities.

U.S. Patent Number 5,705,928

Inventor: Ronald L. Haner

Issued: Jan. 6, 1998

A sample delivery system for a flow-through NMR analysis is provided, which utilizes pressurized gas as a means for conveying a sample into and out of an NMR spectrometer. Two sources of gas pressure, a forward pressure and back pressure, oppose the sample within the tubing of the sample delivery system and the tubing of the flow-through system which are operatively coupled together. Conveyance of the sample in any direction within the tubing is achieved by adjusting the pressure differential. Precise positioning of the sample in the magnetic field center and complete removal of the sample from the NMR spectrometer when analysis is complete are achieved by using a signal processor which receives signals from the NMR detector or other detectors positioned along the length of the tubing. These signals provide an indication of the position of the sample in the tubing. The signal processor uses this

McMurtry Doc.No. GM-1-mv, 9 January 2002

information to adjust the forward and back pressure, thereby achieving the desired positioning of the sample.

U.S. Patent Number 5,841,136

Inventor: Armin Holle et al.

Issued: Nov. 24, 1998

A system and a method for the introduction of sample supports, which hold large numbers of analysis samples, into the ion source region of a mass spectrometer. The sample supports are especially intended for the ionization method using matrix-assisted desorption through laser bombardment (MALDI). The system consists of using an evacuable, sealable and removable cassette which, instead of using a through-passage lock chamber with two lock valves, can be attached in a simple manner to the entrance opening for the ion source of the mass spectrometer. Only the entrance opening has a lock valve, and the expensive second lock valve in the lock chamber is no longer needed. The cassette can also be used for protected transport and for storage of the sample supports, and in particular for storage of the samples under protective gas or vacuum.

U.S. Patent Number US 6,177,991 B1

Inventor: Tetsuo Okuda

Issued: Jan. 23, 2001

A measuring device such as a spectrometer uses an automatic sample changer for carrying a plurality of samples. The automatic sample changer may include a rotary circular disk rotatable around its central shaft by a stepping motor for changing positions of the samples which are positioned in a circle around the central shaft of the disk. A memory device preliminarily storing control data for each of different kinds of automatic sample changers is provided. The automatic sample changer, when connected to a control unit in the main body, serves to receive control signals for controlling motions of the motor and to transmit data stored in the memory device through a connector. The main body of the measuring device contains a control unit which serves to read out the control data from the memory device, to use the received control data to generate the control signal and to transmit the generated control signal to the automatic sample changer.

McMurtry Doc.No. GM-1-mv, 9 January 2002

U.S. Patent Number US 6,182,012 B1

Inventor: Donald V. Kenny

Issued: Feb. 13, 2001

A manipulator apparatus, system and method for measuring analyses present in sample tubes. The manipulator apparatus includes a housing having a central bore with an inlet end and outlet end; a plunger mechanism with at least a portion thereof slideably disposed for reciprocal movement within the central bore, the plunger mechanism having a tubular gas channel with an inlet end and an outlet end, the gas channel inlet end disposed in the same direction as said inlet end of the central bore, wherein the inlet end of said plunger mechanism is adapted for movement so as to expel a sample tube inserted in the bore at the outlet end of the housing, the inlet end of the plunger mechanism is adapted for connection to gas supply; a first seal is disposed in the housing for sealing between the central bore and the plunger mechanism; a second seal is disposed at the outlet end of the housing for sealing between the central bore and a

McMurtry Doc.No. GM-1-mv, 9 January 2002

sample tube; a holder mounted on the housing for holding the sample tube; and  
a biasing mechanism for returning the plunger mechanism to a starting position.



U.S. Patent Number US 6,190,316 B1

Inventor: Yukiko Hirabayashi

Issued: Feb. 20, 2001

A living body fluid analyzing system includes a microdialysis for sending a first solution having an osmotic pressure which is substantially similar to a osmotic pressure of a body fluid into a living body and extracting a second solution from the living body. A first flow passage is provided in which the second solution from the microdialysis flows and a second flow passage is provided which mixes the second solution with an organic solution.

Furthermore, there is provided a gas source and a gas flow controller which controls a flow quantity of the gas from the gas source and a third flow passage in which a gas introduced from the gas source flows. An ion source is provided having an orifice for spraying and ionizing the second solution from the second flow passage at an end of the third flow passage, and a mass spectrometer is provided for mass-analyzing the ions sprayed from the orifice.

While these mass spectrometer sampling devices may be suitable for the purposes for which they were designed, they would not be as suitable for the purposes of the present invention, as hereinafter described.

## **SUMMARY OF THE PRESENT INVENTION**

A primary object of the present invention is to provide an environmental sampler for mass spectrometers that enables small amounts of gases or fluids to enter the vacuum system of a mass spectrometer under various environmental conditions.

Another object of the present invention is to provide an environmental sampler for mass spectrometers wherein the flow of said gases or fluids is regulated by the reciprocating movement of two parallel rods traveling therethrough and driven by a stepper motor.

Yet another object of the present invention is to provide an environmental sampler for mass spectrometers in which the rods have hydraulic seals and O-rings to form a seal and rod assembly, said seal and rod system including small calibrated leaks to provide flow therethrough into the sampler vacuum chamber during rod travel.

Still yet another object of the present invention is to provide an environmental sampler for mass spectrometers having a removable external plenum, which, in tandem with an external pump allows for directional flow of gases or fluids over the sampler rod from a selected region of interest.

Still another object of the present invention is to provide an environmental sampler for mass spectrometers wherein the sampler plenum permits relatively small amounts of sample or standard to be analyzed when statically confined therein.

Still yet another object of the present invention is to provide an environmental sampler for mass spectrometers having an internal standard reservoir that is pressure-compensated by a resilient bladder member.

Another object of the present invention is to provide an environmental sampler for mass spectrometers which provides sample volumes in consistent

ratios from the external and internal sources, via the pressure compensated sample reservoir.

Yet another object of the present invention is to provide very small amounts of sample that are rapidly expanded so that initial sample temperatures can be quite high without serious effect on the mass spectrometer.

Yet another object of the present invention is to provide an environmental sampler for mass spectrometers having a removable external vacuum port to ambient that allows pumping and monitoring of a sample/standard waste vacuum within the mass spectrometer pressure housing.

Another object of the present invention is to provide an environmental sampler for mass spectrometers that is economical in cost to manufacture and operate.

Yet another object of the present invention is to provide an environmental sampler for mass spectrometers that is simple and easy to use.

Additional objects of the present invention will appear as the description proceeds.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

The present invention overcomes the shortcomings of the prior art by providing an environmental sampler for mass spectrometers.

To the accomplishment of the above and related objects, this invention may be embodied in the form illustrated in the accompanying drawings, attention being called to the fact, however, that the drawings are illustrative only, and that changes may be made in the specific construction illustrated and described within the appended claims.

## **BRIEF DESCRIPTION OF THE DRAWING FIGURES**

In order that the invention may be more fully understood, it will now be described, by way of example, with reference to the accompanying drawing in which:

FIGURE 1 is a rear perspective view of the present invention.

FIGURE 2 is a side view of the present invention.

FIGURE 3 is a front perspective view of the present invention.

FIGURE 4 is a perspective view of the plenum of the present invention.

FIGURE 5 is a cross sectional side view of the plenum assembly.



FIGURE 6 is an exploded perspective view of the sampler and the plenum assembly`.

FIGURE 7 is a cross sectional side view of the present invention.

FIGURE 8 is a cross sectional side view of the present invention.

FIGURE 9 is a cross sectional top view of the present invention.

FIGURE 10 is a cross sectional side view of the present invention.

FIGURE 11 is a flow chart of the operation of the present invention.

The foregoing and other objects and advantages will appear from the description to follow. In the description reference is made to the accompanying drawing, which forms a part hereof, and in which is shown by way of illustration of specific embodiments in which the invention may be practiced. These embodiments will be described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that structural changes may be made without departing from the scope of the invention. In the accompanying drawings, like reference characters designate the same or similar parts throughout the several views.

## DESCRIPTION OF THE REFERENCED NUMERALS

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, the figures illustrate the Environmental Sampler for Mass Spectrometer of the present invention. With regard to the reference numerals used, the following numbering is used throughout the various drawing figures.

- 10 environmental sampler for mass spectrometer
- 12 environmental sampler housing
- 14 environmental sampler housing attachment o-ring grooves
- 16 vacuum port assembly
- 18 spacer
- 20 rotating cap assembly
- 22 stepper motor
- 24 stepper motor gear box
- 26 sprocket gear

28	lead screw
30	lead nut
32	driving rod
34	bearing
36	sample port
38	vacuum port
40	retaining ring
42	sampler rod
46	retaining ring
48	pressure-compensating bladder
50	plenum
52	inlet/outlet port
54	attachment ring
56	plenum chamber
58	sampler rod seal
60	vacuum chamber (sample/standard)
62	internal standard reservoir

- 64 threaded stud
- 66 o-ring seal
- 68 operational flowchart
- 70 vacuum chamber (waste)

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

The following discussion describes in detail one embodiment of the invention and several variations of that embodiment. This discussion should not be construed, however, as limiting the invention to those particular embodiments. Practitioners skilled in the art will recognize numerous other embodiments as well. For a definition of the complete scope of the invention, the reader is directed to the appended claims.

Figure 1 is a perspective rear view of the present invention showing the environmental sampler of the present invention. The device has a housing 12 with fastening means 14 for attaching to a mass spectrometer. The environmental sampler 12 has a stepper motor 22 and a stepper motor gear box 24 engaging a sprocket gear 26 driving a lead screw 28 having connection with a lead nut 30 connecting said lead screw 28 with a guide rod 32. The guide rod 32 advances and retracts according to the stepper motor 22 driven by control signals. The guide rod 32 has a guide rod bearing 34 to aid in smooth

longitudinal displacement. The housing also has a sampler port 36 wherein environmental matter is introduced to the mass spectrometer for analysis. To evacuate the environmental sampler a vacuum waste port 38 is provided.

Also shown is vacuum port assembly 16 having spacer 18 and rotating cap assembly 20.

Figure 2 is a side view of the present invention. Shown is the environmental sampler having a vacuum port assembly 16 spacer 18 and rotating cap assembly 20 for a mass spectrometer waste vacuum. The spacer element 18 provides for gas flow by holding back the spring of the internal o-ring seal. The rotating cap assembly 20 provides for the engagement/disengagement of the internal o-ring seal. A vacuum may be drawn in the disengaged position. The vacuum may then be sealed in the engaged position. Also shown is the stepper motor 22 and stepper motor gear box 24 that drives the driving rod 32 by means of lead nut 30 through bearing 34.

Figure 3 is a perspective view of the present invention. The pressure compensating bladder 48 is adjacent the internal standard reservoir 62 and assumes a concave or convex profile as dictated by the external pressure. The standard can be of any aqueous or organic solvent of known composition. The internal standard is sampled alternately with the external environment to provide the user with a benchmark as to the accuracy of sampling by constantly sampling a known composition thus allowing the user and/or computer to calibrate accordingly.

Figure 4 is a perspective view of the plenum assembly 50. The removable external plenum 50 allows for directional flow of gas or fluid from the external environment to pass over the sampler rod which is encased by the plenum assembly 50. The plenum assembly has an inlet and outlet port 52 providing access to an internal cavity wherein the sampler rod 42 moves into and out of under the control of the stepper motor 22. The plenum assembly is mounted to the environmental sampler housing 12 over the sampler rod 42 by using the attachment ring 54 in place of the retaining ring 40.



Figure 5 is cross sectional side view of the plenum assembly 50. The plenum produces by means of the inlet and outlet port 52 an even flow of sample over all surfaces of the sampler rod 42. It also creates a directed flow impinging on the sampler rod seal 58. This minimizes the dead volume around the sampler rod 42 and delivers a constantly fresh supply of sample to the system. The small volume within the plenum chamber 56 allows for a rapid purge of the system when necessary. The plenum also provides for the sampling of a static volume contained therein.

Figure 6 is an exploded view of the environmental sampler 10 and the plenum assembly 50. The plenum assembly 50 has inlet and outlet ports 52 providing access to the plenum chamber 56 and attaches to the environmental sampler housing 12 by means of the plenum attachment ring 54 which replaces the retainer ring 40 of the sampler and has a silicone gasket or other such sealing means located therebetween.

Figure 7 is a sectional view of the environmental sampler 10 of the present invention showing the front sampler rod 42 and the rear driving rod 32 with a ball joint connection therebetween encompassed by the housing 12. The stepper motor 22 by means of the stepper motor gear box 24 moves the driving rod 32 by means of lead nut 30 which in turn controls the movement of the sampler rod 42.

Figure 8 is a cross sectional side view of the present invention, taken from figure 2 as indicated showing the sample vacuum chamber 60 and sampler rod 42. The sample is directed by the mass spectrometer vacuum through the sample port 36.

Figure 9 is a cross sectional side view of the present invention showing the internal standard reservoir 62 in relation to the pressure compensating bladder 48 and sampler rod 42. The sampler environmental material and standard reservoir material are drawn into the mass spectrometer through the vacuum chamber 60.

Figure 10 is a cross sectional side view of the present invention with the waste vacuum port assembly 16 shown in detail. The waste vacuum port assembly has a spacer 18 and rotating cap assembly 20. The rotating cap assembly is connected to an O-ring seal 66 by a threaded stud 64 that provides for the engagement or disengagement of the O-ring seal 66. In the disengaged position vacuum may be drawn.

Figure 11 is a flow chart 68 showing the basic operation of the present invention. The stepper motor 22 under a control signal moves the driving rod 32 which in turn moves the sampler rod 42 having a plurality of engineered micro leaks toward a housing aperture having a retaining ring 40 attached thereto. The sampler rod micro leaks pick up sample material from the internal standard reservoir 62 which are conducted to the mass spectrometer by means of sampler port 60. On the return stroke the sampler rod micro leaks pick up environmental sample material which is conducted to the mass spectrometer by means of vacuum chamber 60.